

RS Agrimix Evolution Mixers

2015 Specification

Standard Features

- ✓ 2 speed gearbox
- ✓ Electronic in cab control for 2 speed gearbox
- ✓ Steel straw ring in the tub
- ✓ Front platform
- ✓ 1.1 metre wide front door
- ✓ Tall augers
- ✓ 2 knife positions on augers for more aggressive chopping
- ✓ Weigh and tare weighing system
- ✓ Hydraulically braked axle
- ✓ LED rear lights
- ✓ All hydraulic motors drive through rotex anti shock couplings
- ✓ Conveyors and elevators feature external greaseable bearings
- ✓ All conveyor and elevators have easy adjustment for tracking
- ✓ Elevators have electric in cab controls (optional on all other feed out systems)
- ✓ Commercial braked axles on twin auger mixers (not with 215/75-17.5 wheel option)

Options

- ☑ Programmable weighing system
- ☑ TMR Tracker pc based feed management system (www.tmrtracker.com)
- ☑ Loader cab remote weight read out or control
- ☑ Multiple door positions
- ☑ Conveyor to front or rear
- ☑ Conveyor with option of timed shuttle to feed both sides simultaneously
- ☑ Sliding conveyor to 350mm each side
- ☑ Elevators from 0.7m to 1.7m in length
- ☑ Belt or chain and slat construction for conveyor and elevator
- ☑ Varilift lifting front conveyor to feed to both left and right sides
- ☑ Hi power tub magnets (retrofit kits available)
- ☑ Hydraulic counter knives
- ☑ Hydraulic folding top extension
- ☑ Wheels, multiple options for yard or road usage including anti puncture foam filled
- ☑ Axles, twin or triple steering options
- ☑ Commercial axles and brakes with oil or air load sensing options
- ☑ Stainless steel edging or overlay to auger
- ☑ Stainless steel lining to tub